



Mercedes-Benz

## CLS-Class Shooting Brake CLS 350 CDI BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V6
Model variant number	218923
Restriction code	
Market launch	2012.10
Total displacement (cc)	2.987
Rated output (kW [hp] at rpm) 1)	195 [265]/3.800
Rated torque (Nm at rpm) 1)	620/1.600 - 2.400
Compression ratio	15,5 : 1
Acceleration 0-100 km/h (s)	6,6
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,647

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	80/9,0
Fuel consumption, urban 2)	7,5-7,3 l/100 km
Fuel consumption, extra-urban 2)	5,4-5,3 l/100 km
Fuel consumption, combined 2)	6,1-6,0 l/100 km
CO2 emissions combined (g/km) 2)	162-159
Efficiency class 3)	B
Emissions standard	Euro 5

Suspension and steering	
Front axle	Multi-link
Rear axle	Multi-link
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Air spring, Double-tube gas pressure
Tyres/wheels, front	245/45 R 17
Tyres/wheels, rear	245/45 R 17
Steering gear - type	Rack-and-pinion
Power steering	Speed-dependent, electro-mechanical
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance category	
Insurance category liability/FC/partial	22/28/28



## CLS-Class Shooting Brake CLS 350 CDI BlueEFFICIENCY.

Dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 4)	1.910/525
Perm. gross vehicle weight (kg)	2.435
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load unbraked/braked [at 12%]/braked [at 8%] (kg)	750/2.100/k. A.
Permissible drawbar load (kg)	84
Turning circle (m)	11,27
Vehicle length (mm)	4.956
Vehicle width (mm)	1.881
Vehicle height at kerb weight (mm)	1.416
Cd value	0,29
Track width, front (mm)	1.596
Track width, rear (mm)	1.626
Wheelbase (mm)	2.874

- 1) Rated output and torque figures in accordance with Directive 80/1269/EEC in the currently applicable version.
- 2) The figures shown were obtained in accordance with the prescribed measuring process (Directive [EC] 715/2007) in the currently applicable version. Note according to Directive 1999/94/EC in the currently applicable version: The figures are not based on an individual vehicle and do not constitute part of the product offer, they are provided solely for purposes of comparison between different vehicle models.
- 3) Established on the basis of measured CO<sub>2</sub> emissions, and taking the vehicle mass into account.
- 4) Figures according to Directive 92/21/EC, version 95/48/EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard-specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



Mercedes-Benz

## CLS-Class Shooting Brake CLS 350 CDI 4MATIC BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V6
Model variant number	218993
Restriction code	
Market launch	2012.11
Total displacement (cc)	2.987
Rated output (kW [hp] at rpm) 1)	195 [265]/3.800
Rated torque (Nm at rpm) 1)	620/1.600 - 2.400
Compression ratio	15,5 : 1
Acceleration 0-100 km/h (s)	6,7
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive	Permanent four-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,647

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	80/9,0
Fuel consumption, urban 2)	8,0-7,9 l/100 km
Fuel consumption, extra-urban 2)	6,0-5,9 l/100 km
Fuel consumption, combined 2)	6,7-6,6 l/100 km
CO2 emissions combined (g/km) 2)	176-174
Efficiency class 3)	C
Emissions standard	Euro 5

Suspension and steering	
Front axle	Multi-link
Rear axle	Multi-link
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Air spring, Double-tube gas pressure
Tyres/wheels, front	245/45 R 17
Tyres/wheels, rear	245/45 R 17
Steering gear - type	Rack-and-pinion
Power steering	Speed-dependent, electro-mechanical
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance category	
Insurance category liability/FC/partial	22/28/28



## CLS-Class Shooting Brake CLS 350 CDI 4MATIC BlueEFFICIENCY.

Dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 4)	1.970/525
Perm. gross vehicle weight (kg)	2.495
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load unbraked/braked [at 12%]/braked [at 8%] (kg)	750/2.100/k. A.
Permissible drawbar load (kg)	84
Turning circle (m)	11,27
Vehicle length (mm)	4.956
Vehicle width (mm)	1.881
Vehicle height at kerb weight (mm)	1.416
Cd value	0,29
Track width, front (mm)	1.596
Track width, rear (mm)	1.626
Wheelbase (mm)	2.874

1) Rated output and torque figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring process (Directive [EC] 715/2007) in the currently applicable version. Note according to Directive 1999/94/EC in the currently applicable version: The figures are not based on an individual vehicle and do not constitute part of the product offer, they are provided solely for purposes of comparison between different vehicle models.

3) Established on the basis of measured CO<sub>2</sub> emissions, and taking the vehicle mass into account.

4) Figures according to Directive 92/21/EC, version 95/48/EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard-specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



## CLS-Class Shooting Brake CLS 350 BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V6
Model variant number	218959
Restriction code	
Market launch	2012.10
Total displacement (cc)	3.498
Rated output (kW [hp] at rpm) 1)	225 [306]/6.500
Rated torque (Nm at rpm) 1)	370/3.500 - 5.250
Compression ratio	12,0 : 1
Acceleration 0-100 km/h (s)	6,7
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,823

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	80/9,0
Fuel consumption, urban 2)	9,8-9,7 l/100 km
Fuel consumption, extra-urban 2)	5,9-5,8 l/100 km
Fuel consumption, combined 2)	7,4-7,3 l/100 km
CO2 emissions combined (g/km) 2)	172-169
Efficiency class 3)	C
Emissions standard	Euro 5

Suspension and steering	
Front axle	Multi-link
Rear axle	Multi-link
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Air spring, Double-tube gas pressure
Tyres/wheels, front	245/45 R 17
Tyres/wheels, rear	245/45 R 17
Steering gear - type	Rack-and-pinion
Power steering	Speed-dependent, electro-mechanical
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance category	
Insurance category liability/FC/partial	22/28/28



## CLS-Class Shooting Brake CLS 350 BlueEFFICIENCY.

Dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 4)	1.830/525
Perm. gross vehicle weight (kg)	2.355
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load unbraked/braked [at 12%]/braked [at 8%] (kg)	750/2.100/k. A.
Permissible drawbar load (kg)	84
Turning circle (m)	11,27
Vehicle length (mm)	4.956
Vehicle width (mm)	1.881
Vehicle height at kerb weight (mm)	1.416
Cd value	0,29
Track width, front (mm)	1.596
Track width, rear (mm)	1.626
Wheelbase (mm)	2.874

1) Rated output and torque figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring process (Directive [EC] 715/2007) in the currently applicable version. Note according to Directive 1999/94/EC in the currently applicable version: The figures are not based on an individual vehicle and do not constitute part of the product offer, they are provided solely for purposes of comparison between different vehicle models.

3) Established on the basis of measured CO<sub>2</sub> emissions, and taking the vehicle mass into account.

4) Figures according to Directive 92/21/EC, version 95/48/EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard-specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



## CLS-Class Shooting Brake CLS 63 AMG.

Engine and performance (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Arrangement/no. of cylinders	V8
Model variant number	218974
Restriction code	
Market launch	2012.10
Total displacement (cc)	5.461
Rated output (kW [hp] at rpm) 1)	386 [525]/5.250-5.750
Rated torque (Nm at rpm) 1)	700/1.700 - 5.000
Compression ratio	10,0 : 1
Acceleration 0-100 km/h (s)	4,4
Top speed (km/h)	250

Power transmission (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Drive	Rear-wheel drive
Transmission	AMG SPEEDSHIFT MCT 7-speed sports transmission
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,65

Fuel and emissions (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Tank capacity/reserve (l)	66/14
Fuel consumption, urban 2)	14,0-14,0 l/100 km
Fuel consumption, extra-urban 2)	7,8-7,8 l/100 km
Fuel consumption, combined 2)	10,1-10,1 l/100 km
CO2 emissions combined (g/km) 2)	235-235
Efficiency class 3)	F
Emissions standard	Euro 5

Suspension and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Spring strut with coil spring, Monroe CES adjustable damping/Air spring, Monroe CES adjustable damping
Tyres/wheels, front	255/35 ZR19 (96Y) XL
Tyres/wheels, rear	285/30 ZR19 (98Y) XL
Steering gear - type	Electric steering with AMG steering control and constant sports ratio
Power steering	Speed-dependent, electro-mechanical
Front brakes	Composite discs, internally ventilated and perforated
Rear brakes	one-piece, externally ventilated and perforated

Vehicle identification	
Insurance category	
Insurance category liability/FC/partial	22/32/32



## CLS-Class Shooting Brake CLS 63 AMG.

Dimensions and weights (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Kerb weight/payload (kg) 4)	1.955/660
Perm. gross vehicle weight (kg)	2.540
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load unbraked/braked [at 12%]/braked [at 8%] (kg)	-/-/k. A.
Permissible drawbar load (kg)	-
Turning circle (m)	11,30
Vehicle length (mm)	5.000
Vehicle width (mm)	1.881
Vehicle height at kerb weight (mm)	1.412
Cd value	0,31
Track width, front (mm)	1.625
Track width, rear (mm)	1.604
Wheelbase (mm)	2.874

1) Rated output and torque figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring process (Directive [EC] 715/2007) in the currently applicable version. Note according to Directive 1999/94/EC in the currently applicable version: The figures are not based on an individual vehicle and do not constitute part of the product offer, they are provided solely for purposes of comparison between different vehicle models.

3) Established on the basis of measured CO<sub>2</sub> emissions, and taking the vehicle mass into account.

4) Figures according to Directive 92/21/EC, version 95/48/EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard-specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



## CLS-Class Shooting Brake CLS 63 AMG.

Engine and performance (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Arrangement/no. of cylinders	V8
Model variant number	218974
Restriction code	0-923 increased power version
Market launch	2012.10
Total displacement (cc)	5.461
Rated output (kW [hp] at rpm) 1)	410 [557]/5.250-5.750
Rated torque (Nm at rpm) 1)	800/2.000 - 4.500
Compression ratio	10,0 : 1
Acceleration 0-100 km/h (s)	4,3
Top speed (km/h)	250

Power transmission (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Drive	Rear-wheel drive
Transmission	AMG SPEEDSHIFT MCT 7-speed sports transmission
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,65

Fuel and emissions (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Tank capacity/reserve (l)	66/14
Fuel consumption, urban 2)	14,0-14,0 l/100 km
Fuel consumption, extra-urban 2)	7,8-7,8 l/100 km
Fuel consumption, combined 2)	10,1-10,1 l/100 km
CO2 emissions combined (g/km) 2)	235-235
Efficiency class 3)	F
Emissions standard	Euro 5

Suspension and steering	
Front axle	Multi-link
Rear axle	Multi-link independent suspension
Springs, front/rear	Spring strut with coil spring, Monroe CES adjustable damping/Air spring, Monroe CES adjustable damping
Tyres/wheels, front	255/35 ZR19 (96Y) XL
Tyres/wheels, rear	285/30 ZR19 (98Y) XL
Steering gear - type	Electric steering with AMG steering control and constant sports ratio
Power steering	Speed-dependent, electro-mechanical
Front brakes	Composite discs, internally ventilated and perforated
Rear brakes	one-piece, externally ventilated and perforated

Vehicle identification	
Insurance category	
Insurance category liability/FC/partial	22/32/32



## CLS-Class Shooting Brake CLS 63 AMG.

Dimensions and weights (AMG SPEEDSHIFT MCT 7-speed sports transmission)	
Kerb weight/payload (kg) 4)	1.955/660
Perm. gross vehicle weight (kg)	2.540
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load unbraked/braked [at 12%]/braked [at 8%] (kg)	-/-/k. A.
Permissible drawbar load (kg)	-
Turning circle (m)	11,30
Vehicle length (mm)	5.000
Vehicle width (mm)	1.881
Vehicle height at kerb weight (mm)	1.412
Cd value	0,31
Track width, front (mm)	1.625
Track width, rear (mm)	1.605
Wheelbase (mm)	2.874

1) Rated output and torque figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring process (Directive [EC] 715/2007) in the currently applicable version. Note according to Directive 1999/94/EC in the currently applicable version: The figures are not based on an individual vehicle and do not constitute part of the product offer, they are provided solely for purposes of comparison between different vehicle models.

3) Established on the basis of measured CO<sub>2</sub> emissions, and taking the vehicle mass into account.

4) Figures according to Directive 92/21/EC, version 95/48/EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard-specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



Mercedes-Benz

## CLS-Class Shooting Brake CLS 250 CDI BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	L4
Model variant number	218903
Restriction code	
Market launch	2012.10
Total displacement (cc)	2.143
Rated output (kW [hp] at rpm) 1)	150 [204]/3.800
Rated torque (Nm at rpm) 1)	500/1.600 - 1.800
Compression ratio	16,2 : 1
Acceleration 0-100 km/h (s)	7,8
Top speed (km/h)	235

Power transmission (7G-TRONIC PLUS)	
Drive	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,647

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	59/8,0
Fuel consumption, urban 2)	6,4-6,3 l/100 km
Fuel consumption, extra-urban 2)	4,8-4,7 l/100 km
Fuel consumption, combined 2)	5,4-5,3 l/100 km
CO2 emissions combined (g/km) 2)	143-139
Efficiency class 3)	A
Emissions standard	Euro 5

Suspension and steering	
Front axle	Multi-link
Rear axle	Multi-link
Springs, front/rear	Coil spring, Double-tube gas pressure with SDD/Air spring, Double-tube gas pressure
Tyres/wheels, front	245/45 R 17
Tyres/wheels, rear	245/45 R 17
Steering gear - type	Rack-and-pinion
Power steering	Speed-dependent, electro-mechanical
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, solid

Vehicle identification	
Insurance category	
Insurance category liability/FC/partial	22/28/28



## CLS-Class Shooting Brake CLS 250 CDI BlueEFFICIENCY.

Dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 4)	1.865/525
Perm. gross vehicle weight (kg)	2.390
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load unbraked/braked [at 12%]/braked [at 8%] (kg)	750/2.100/k. A.
Permissible drawbar load (kg)	84
Turning circle (m)	11,27
Vehicle length (mm)	4.956
Vehicle width (mm)	1.881
Vehicle height at kerb weight (mm)	1.416
Cd value	0,29
Track width, front (mm)	1.596
Track width, rear (mm)	1.626
Wheelbase (mm)	2.874

1) Rated output and torque figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring process (Directive [EC] 715/2007) in the currently applicable version. Note according to Directive 1999/94/EC in the currently applicable version: The figures are not based on an individual vehicle and do not constitute part of the product offer, they are provided solely for purposes of comparison between different vehicle models.

3) Established on the basis of measured CO<sub>2</sub> emissions, and taking the vehicle mass into account.

4) Figures according to Directive 92/21/EC, version 95/48/EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard-specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



Mercedes-Benz

## CLS-Class Shooting Brake CLS 500 4MATIC BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V8
Model variant number	218991
Restriction code	
Market launch	2012.11
Total displacement (cc)	4.663
Rated output (kW [hp] at rpm) 1)	300 [408]/5.000-5.750
Rated torque (Nm at rpm) 1)	600/1.600 - 4.750
Compression ratio	10,5 : 1
Acceleration 0-100 km/h (s)	5,3
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive	Permanent four-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,473

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	80/9,0
Fuel consumption, urban 2)	13,4-13,3 l/100 km
Fuel consumption, extra-urban 2)	7,9-7,8 l/100 km
Fuel consumption, combined 2)	9,9-9,8 l/100 km
CO2 emissions combined (g/km) 2)	231-229
Efficiency class 3)	E
Emissions standard	Euro 5

Suspension and steering	
Front axle	Multi-link
Rear axle	Multi-link
Springs, front/rear	Air spring, Damper with damper valve/Air spring, Damper with damper valve
Tyres/wheels, front	255/40 R 18
Tyres/wheels, rear	255/40 R 18
Steering gear - type	Rack-and-pinion
Power steering	Speed-dependent, electro-mechanical
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance category	
Insurance category liability/FC/partial	22/28/28



## CLS-Class Shooting Brake CLS 500 4MATIC BlueEFFICIENCY.

Dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 4)	2.005/525
Perm. gross vehicle weight (kg)	2.530
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load unbraked/braked [at 12%]/braked [at 8%] (kg)	750/2.100/k. A.
Permissible drawbar load (kg)	84
Turning circle (m)	11,27
Vehicle length (mm)	4.956
Vehicle width (mm)	1.881
Vehicle height at kerb weight (mm)	1.421
Cd value	0,31
Track width, front (mm)	1.596
Track width, rear (mm)	1.626
Wheelbase (mm)	2.874

1) Rated output and torque figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring process (Directive [EC] 715/2007) in the currently applicable version. Note according to Directive 1999/94/EC in the currently applicable version: The figures are not based on an individual vehicle and do not constitute part of the product offer, they are provided solely for purposes of comparison between different vehicle models.

3) Established on the basis of measured CO<sub>2</sub> emissions, and taking the vehicle mass into account.

4) Figures according to Directive 92/21/EC, version 95/48/EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard-specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly



Mercedes-Benz

## CLS-Class Shooting Brake CLS 500 BlueEFFICIENCY.

Engine and performance (7G-TRONIC PLUS)	
Arrangement/no. of cylinders	V8
Model variant number	218973
Restriction code	
Market launch	2012.10
Total displacement (cc)	4.663
Rated output (kW [hp] at rpm) 1)	300 [408]/5.000-5.750
Rated torque (Nm at rpm) 1)	600/1.600 - 4.750
Compression ratio	10,5 : 1
Acceleration 0-100 km/h (s)	5,3
Top speed (km/h)	250

Power transmission (7G-TRONIC PLUS)	
Drive	Rear-wheel drive
Transmission	7G-TRONIC PLUS
Ratios	4,38/2,86/1,92/1,37/1,00/0,82/0,73/R1 3,42/R2 2,23
Final-drive ratio	2,473

Fuel and emissions (7G-TRONIC PLUS)	
Tank capacity/reserve (l)	80/9,0
Fuel consumption, urban 2)	12,8-12,7 l/100 km
Fuel consumption, extra-urban 2)	7,2-7,1 l/100 km
Fuel consumption, combined 2)	9,3-9,2 l/100 km
CO2 emissions combined (g/km) 2)	216-214
Efficiency class 3)	E
Emissions standard	Euro 5

Suspension and steering	
Front axle	Multi-link
Rear axle	Multi-link
Springs, front/rear	Air spring, Damper with damper valve/Air spring, Damper with damper valve
Tyres/wheels, front	255/40 R 18
Tyres/wheels, rear	255/40 R 18
Steering gear - type	Rack-and-pinion
Power steering	Speed-dependent, electro-mechanical
Front brakes	Discs, internally ventilated and perforated
Rear brakes	Discs, internally ventilated

Vehicle identification	
Insurance category	
Insurance category liability/FC/partial	22/28/28



## CLS-Class Shooting Brake CLS 500 BlueEFFICIENCY.

Dimensions and weights (7G-TRONIC PLUS)	
Kerb weight/payload (kg) 4)	1.955/525
Perm. gross vehicle weight (kg)	2.480
Max. roof load (kg)	100
Boot capacity (VDA) min/max (l)	
perm. trailer load unbraked/braked [at 12%]/braked [at 8%] (kg)	750/2.100/k. A.
Permissible drawbar load (kg)	84
Turning circle (m)	11,27
Vehicle length (mm)	4.956
Vehicle width (mm)	1.881
Vehicle height at kerb weight (mm)	1.421
Cd value	0,31
Track width, front (mm)	1.596
Track width, rear (mm)	1.626
Wheelbase (mm)	2.874

1) Rated output and torque figures in accordance with Directive 80/1269/EEC in the currently applicable version.

2) The figures shown were obtained in accordance with the prescribed measuring process (Directive [EC] 715/2007) in the currently applicable version. Note according to Directive 1999/94/EC in the currently applicable version: The figures are not based on an individual vehicle and do not constitute part of the product offer, they are provided solely for purposes of comparison between different vehicle models.

3) Established on the basis of measured CO<sub>2</sub> emissions, and taking the vehicle mass into account.

4) Figures according to Directive 92/21/EC, version 95/48/EC ( kerb weight with fuel tank 90% full, driver, 68 kg, and luggage, 7 kg ) for standard-specification vehicles. Optional extras and accessories will generally increase this figure and reduce the payload capacity accordingly